

EC Declaration of Conformity

(Construction Products Directive 89/106/EEC)

Rockfon Group

Hovedgaden 501

DK-2640 Hedehusene Denmark

Phone +45 4656 2122 Fax +45 4656 4030 www.rockfon.com

Declares under his responsibility that the following suspended ceiling membrane component for use internally in buildings

Coloral

manufactured in the EU, with a nominal thickness range of 15-40mm, complies with requirements as specified in the European Standard for suspended ceilings EN 13964:2004 (Annex ZA).

Evaluated and declared product properties include:

- ☐ Reaction to Fire Euroclass A2-s1,d0
- ☐ Release of Formaldehyde Class E1
- ☐ Flexural Tensile Strength (membrane width \leq 700mm) 1 / C / ON
(membrane width $>$ 700mm) NPD
- ☐ Weighted Sound Absorption Coefficient:

Thickness	Practical Sound Absorption Coefficients, α_p (E-200 mounting)						Declaration	
	125Hz	250Hz	500Hz	1kHz	2kHz	4kHz	α_w	Class
15mm							NPD	
20mm	0,35	0,75	1,00	0,90	0,95	1,00	0,95	A
25mm	0,50	0,70	0,75	0,85	0,90	0,85	0,85	B
40mm	0,60	0,85	0,95	1,00	1,00	1,00	1,00	A

This declaration of conformity is supported by the EC Certificate of Conformity number 0749-CPD-BC1-533-1817-0005-02 issued by BCCA, Rue d'Arlon 53, B-1040 Brussels.

 Herman Voertmann
Managing Director
Rockfon Group

activeceilings™

ROCKWOOL
Rockfon®
ACTIVATE YOUR CEILING